

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the application:

5    **Listing of Claims:**

1. (previously presented)    An apparatus for performing motion compensation when decoding an incoming video bit stream including a plurality of frames having first macroblocks encoded using block-matching motion compensation and second macroblocks encoded using global motion compensation, the apparatus comprising:

10

an interpolation unit for performing interpolation operations on each macroblock contained in each frame of the incoming video stream; and

15

a multiplexer selecting an inputted macroblock motion vector or an inputted global motion vector and outputting the selected macroblock motion vector or the selected global motion vector to the interpolation unit;

wherein when processing a current macroblock,

20

if the current macroblock is encoded using block-matching motion compensation, the interpolation unit performs the interpolation operations according to the macroblock motion vector; and

25

if the current macroblock is encoded using global motion compensation, the interpolation unit performs the interpolation operations according to the global motion vector on a per-macroblock basis.

2. (original)    The apparatus of claim 1, further comprising a translation unit for

converting global motion parameters associated with a current frame of the incoming video stream into the global motion vector for use by the interpolation unit.

3. (original) The apparatus of claim 2, wherein when processing the current  
5 macroblock, if the current macroblock is encoded using block-matching motion compensation, the interpolation unit performs the interpolation operations according to at least one macroblock motion vector contained in the current macroblock.

4. (previously presented) The apparatus of claim 3, further comprising:

10

a block-matching motion vector storage unit for storing the macroblock motion vector extracted from each macroblock encoded using block-matching motion compensation; and

15

a global motion vector storage unit for storing the global motion vector output by the translation unit;

20

wherein when performing the interpolation operations on macroblocks encoded using block-matching motion compensation, the multiplexer outputs the macroblock motion vector stored in the macroblock motion vector storage unit to the interpolation unit, and when performing the interpolation operations on macroblocks encoded using global motion compensation, the multiplexer outputs the global motion vector stored in the global motion vector storage unit to the interpolation unit.

25

5. (original) The apparatus of claim 1, wherein the interpolation operations comprise luminance and chrominance interpolation operations.

6. (original) The apparatus of claim 5, wherein when performing the luminance interpolation operations on macroblocks encoded using block-matching motion compensation, the interpolation unit uses half-pel precision.
- 5 7. (original) The apparatus of claim 5, wherein when performing the chrominance interpolation operations on macroblocks encoded using block-matching motion compensation, the interpolation unit uses half-pel precision.
8. (original) The apparatus of claim 5, wherein when performing the luminance  
10 interpolation operations on macroblocks encoded using global motion compensation, the interpolation unit uses half-pel precision.
9. (previously presented) The apparatus of claim 5, wherein when performing the chrominance interpolation operations on macroblocks encoded using global motion  
15 compensation, the interpolation unit uses quarter-pel precision.
10. (original) The apparatus of claim 1, wherein the video decoder is capable of processing an incoming MPEG-4 video stream.
- 20 11. (previously presented) The apparatus of claim 10, wherein the video decoder is for processing only an incoming MPEG-4 video stream having a no\_of\_sprite\_warping\_point parameter set to either 0 or 1.
12. (original) The apparatus of claim 1, wherein when performing the interpolation  
25 operations, the interpolation unit uses a bilinear interpolation process.
13. (previously presented) A method of processing an incoming video bit stream comprising a plurality of frames, the plurality of frames including first macroblocks

5 encoded using block-matching motion compensation and second macroblocks  
encoded using global motion compensation, the video bit stream including  
macroblock motion vectors indicating motion vectors of the first macroblocks and  
global motion parameters associated with the plurality of frames indicating a motion  
vector of each pixel in the second macroblocks, the method comprising:

10 if a current macroblock is encoded using block-matching motion compensation,  
utilizing an interpolation unit to perform the interpolation operations according  
to macroblock motion vector; and

if a current macroblock is encoded using global motion compensation, utilizing the  
interpolation unit to perform the interpolation operations according to a global  
motion vector which is derived from the video bit stream and is in a form  
substantially identical to that of the macroblock motion vector.

15 14. (original) The method of claim 13, further comprising converting global motion  
parameters associated with a current frame of the incoming video stream into the  
global motion vector.

20 15. (original) The method of claim 13, further comprising if the current macroblock is  
encoded using block-matching motion compensation, performing the interpolation  
operations according to a macroblock motion vector contained in the current  
macroblock.

25 16. (original) The method of claim 13, wherein the interpolation operations comprise  
luminance and chrominance interpolation operations.

17. (original) The method of claim 16, wherein when performing the luminance

interpolation operations on macroblocks encoded using block-matching motion compensation, using half-pel precision.

18. (original) The method of claim 16, wherein when performing the chrominance  
5 interpolation operations on macroblocks encoded using block-matching motion compensation, using half-pel precision.

19. (original) The method of claim 16, wherein when performing the luminance  
interpolation operations on macroblocks encoded using global motion compensation,  
10 using half-pel precision.

20. (previously presented) The method of claim 16, wherein when performing the  
chrominance interpolation operations on macroblocks encoded using global motion  
compensation, using quarter-pel precision.

15 21. (original) The method of claim 13, wherein the method is capable of processing an incoming MPEG-4 video stream.

22. (previously presented) The method of claim 13, wherein the method is for  
20 processing only an incoming MPEG-4 video stream having a no\_of\_sprite\_warping\_point parameter set to either 0 or 1.

23. (original) The method of claim 13, wherein when performing the interpolation  
operations, using a bilinear interpolation process.

25 24. (previously presented) A predicted image synthesizer in a video decoder for decoding a video bit stream and generating a predicted image, the video bit stream including a plurality of frames having first macroblocks encoded using block-matching

compensation and second macroblocks encoded using global motion compensation, the video bit stream including macroblock motion vectors indicating motion vectors of the first macroblocks and global motion parameters associated with the plurality of frames indicating a motion vector of each pixel in the second macroblocks, the  
5 predicted image synthesizer comprising:

a translation unit receiving the global motion parameters, and translating the global motion parameters into a global motion vector which is in a form substantially  
10 identical to that of the macroblock motion vector,

a multiplexer selecting an inputted macroblock motion vector or the inputted global motion vector which is in a form substantially identical to that of the  
15 macroblock motion vector and outputting the selected macroblock motion vector or the selected global motion vector which is in a form substantially identical to that of the macroblock motion vector; and

an interpolation unit for receiving a decoded image which is a previously decoded  
20 frame, receiving the selected macroblock motion vector or the selected global motion vector which is in a form substantially identical to that of the macroblock motion vector outputted by the multiplexer, performing interpolation operations, and generating the prediction image.

25 25. (original) The predicted image synthesizer of claim 24, further comprising a demultiplexer receiving the macroblock motion vectors and global motion parameters, and respectively outputting the macroblock motion vectors and the global motion parameters, the global motion parameters are sent to the translation

unit and translated into a global motion vector which is in a form substantially identical to that of the macroblock motion vector, and the interpolation unit selectively receiving the macroblock motion vector or the global motion vector to perform the interpolation operations.

5

26. (original) The predicted image synthesizer of claim 25, wherein the interpolation unit receives the global motion vector when a current macroblock is encoded using global motion compensation.

10 27. (original) The predicted image synthesizer of claim 25, wherein the interpolation operations include a luminance interpolation operation and a chrominance interpolation operation, the interpolation unit uses a first resolution to perform the luminance interpolation operation and uses a second resolution to perform the chrominance interpolation operation.

15

28. (original) The predicted image synthesizer of claim 27, wherein the first resolution is a half-pel resolution, and the second resolution is a quarter-pel resolution.

20 29. (original) The predicted image synthesizer of claim 25, wherein the interpolation unit receives the macroblock motion vector when a current macroblock is encoded using block-matching motion compensation.

25 30. (original) The predicted image synthesizer of claim 29, wherein the interpolation operations include a luminance interpolation operation and a chrominance interpolation operation, and the interpolation unit uses a half-pel resolution to perform both the luminance interpolation operation and the chrominance interpolation operation.

31. (original) The predicted image synthesizer of claim 30, wherein when performing the interpolation operations, the interpolation unit uses a bilinear interpolation process.
- 5 32. (previously presented) The method of claim 13, further comprising performing the interpolation operations according to the global motion vector on a per-macroblock basis when the current macroblock is encoded using global motion compensation.
- 10 33. (previously presented) The predicted image synthesizer of claim 24, wherein the interpolation unit is further for performing the interpolation operations according to the global motion vector on a per-macroblock basis when the current macroblock is encoded using global motion compensation.
- 15 34. (previously presented) The predicted image synthesizer of claim 24, wherein the video decoder is for processing only an incoming MPEG-4 video stream having a no\_of\_sprite\_warping\_point parameter set to either 0 or 1.